

Charger

Type	Compact Charger	Standard Charger	Fast Charger*
Charging current	max. 2 A	max. 4 A	max. 6 A
Voltage range	100-240 V	220-240 V	220-240 V
Size	approx. 160 × 75 × 45 mm	approx. 190 × 86 × 54 mm	approx. 200 × 90 × 60 mm
Cable lengths	AC-Input: approx. 1.5 m. DC-Output: approx. 1.0 m		
Plug	country-specific power plug		
Weight	approx. 600 grams	approx. 800 grams	approx. 1000 grams
Compatibility	Active Line / Active Line Plus / Performance Line / Performance Line CX / Classic + Line compatible via adapter plug		
Charging time			
PowerTube 500:	50 % in approx. 3.5 h. 100 % in approx. 7.5 h	50 % in approx. 2 h. 100 % in approx. 4.5 h	50 % in approx. 1.2 h. 100 % in approx. 3 h
PowerPack 300:	50 % in approx. 2 h. 100 % in approx. 5 h	50 % in approx. 1 h. 100 % in approx. 2.5 h	50 % in approx. 0.7 h. 100 % in approx. 2 h
PowerPack 400:	50 % in approx. 2.5 h. 100 % in approx. 6.5 h	50 % in approx. 1.5 h. 100 % in approx. 3.5 h	50 % in approx. 1 h. 100 % in approx. 2.5 h
PowerPack 500:	50 % in approx. 3.5 h. 100 % in approx. 7.5 h	50 % in approx. 2 h. 100 % in approx. 4.5 h	50 % in approx. 1.2 h. 100 % in approx. 3 h

* The charging current in PowerPack 300 and rechargeable batteries of the Classic + Line is limited to 4A.