

Technical Features of Kiox

MY 2019 Hardware Facts

- Transmissive 1.9-inch colour display with gorilla glass 3 (208 × 274 pixels, 29 × 39 mm active area)
- Operation of the Kiox via the separate "Remote Compact"
- Walk Assist button on the separate control unit
- The display mount is installed on the stem or the bicycle manufacturer has developed a specific holder solution using the modular mounting plate
- Two buttons for on/off and light directly on the display
- Brightness sensor automatically controls the display's backlight by day and night
- Integrated rechargeable battery delivers power in off-board mode for approx. 20 minutes; on-board, it is charged by the eBike rechargeable battery:
- Rugged and IPx7 waterproof when the USB cap is closed
- Micro-AB-USB port can be used by specialist dealers to perform diagnostic tasks, to charge the Kiox rechargeable battery and to charge external devices, such as compatible smartphones
- Temperature range: -5 °C to +40 °C (operating) and -10 °C to +50 °C (storage)

MY 2019 Connectivity Facts

- Bluetooth connectivity (BLE) for heart rate monitors
- Wireless update option available

Other MY 2019 Features

- Displays current power, cadence and heart rate
- Displays current speed in relation to the average speed
- Support for integrated electronic gear shifting from Shimano, Rohloff and enviolo (eShift)
- Summary of the current trip in off-board mode
- Resetting the consumption values for the Drive Unit (trip and range data)
- Displays the charge state of a battery or of both batteries in DualBattery in the status screen
- Service interval display available